
		R Series 5HP		Eng. Data Sheet: CP-R3-V2
		Engineering Data Sheet		Date: 7/25/2019
		Air Cooled, 60Hz		Supersedes: CP-R3-V1
Model Number		BR5 / VR5-6 / VR5-8 / VR5-12 / HR5-3 / HR5-6 / HR5-8 / HR5-12 / HR5D-8 / HR5D-12 / HR5D-25		
Configurator Number		R2-30A		
Description	Units	Product Data		
Compressor Pump				
Pump Model	na	R15B		
Number of Cylinders	na	2		
Bore & Stroke	in.	4-5/8 & 2-1/2 x 3		
Flywheel	OD in.	16.5		
Pulley 125 PSIG	OD in.	7.35		
Pulley 175 PSIG	OD in.	7		
Number of Stages	na	2		
Lubrication	na	Splash Lubricated		
Oil Capacity	qt.	2		
Oil Type	na	AEON AC-HC, ISO 100 Non-Detergent Industrial Lubricant		
Number of Belt Grooves	na	2		
Belt Section	na	B		
Crankcase	na	Cast Iron		
Bearings	na	Tapered Roller		
Cylinder	na	Aluminum with Cast Iron Liner		
Piston 1st Stage	na	Aluminum Alloy		
Piston 2nd Stage	na	Cast Iron		
Valves	na	Disc Valves		
Intake Filter	na	5 Micron		
Main Drive Motor (1)				
Drive Motor Nominal Power	hp(kW)	5 (3.73)		
Voltage (2)	na	208/230/460/575		
Phase	na	1 or 3		
Drive Motor Speed	rpm	1800		
Service Factor	na	1.15		
Motor Insulation Class	na	F		
Drive Motor Full Load Current - 208/1/60 (3)	amps	30.8		
Drive Motor Full Load Current - 230/1/60 (3)	amps	28		
Drive Motor Full Load Current - 208/3/60 (3)	amps	16.7		
Drive Motor Full Load Current - 230/3/60 (3)	amps	15.2		
Drive Motor Full Load Current - 460/3/60 (3)	amps	7.6		
Drive Motor Full Load Current - 575/3/60 (3)	amps	6.1		
Wire Size - 208/1/60 (3,4,5)	awg	8 (4)		
Wire Size - 230/1/60 (3,4,5)	awg	8 (4)		
Wire Size - 208/3/60 (3,4,5)	awg	10 (8)		
Wire Size - 230/3/60 (3,4,5)	awg	12 (8)		
Wire Size - 460/3/60 (3,4,5)	awg	14 (12)		
Wire Size - 575/3/60 (3,4,5)	awg	14 (12)		

- 1) Main Drive Motor performance is based off the standard ODP motor.
- 2) Compressors are voltage specific and must be specified at time of order.
- 3) The amp draws and wire size provided are off general NEC guidelines. For proper breaker and fuses please consult a licensed electrician or electrical contractor.
- 4) Copper wire, 75°C (167°F) maximum temperature rating, 30°C (86°F) ambient temperature
- 5) Values in () is for incoming power line on duplex units.

Due to Gardner Denver's continuing product development program, specifications and materials are subject to change without notice or obligation.

	R Series 5HP										Eng. Data Sheet: CP-R3-V2			
	Engineering Data Sheet										Date: 7/25/2019			
	Air Cooled, 60Hz										Supersedes: CP-R3-V1			
Model Number	<div style="display: flex; justify-content: space-around; text-align: center;"> BR5 VR5-6 VR5-8 VR5-12 HR5-3 HR5-6 HR5-8 HR5-12 HR5D-8 HR5D-12 HR5D-25 </div>													
Configurator Number	R2-30A													
Description	Units	Product Data												
Performance Data (6)														
CFM Delivery @ 125 PSIG (7)	acfm	19.1						38.2						
CFM Delivery @ 175 PSIG (7)	acfm	17.3						34.6						
CFM Displacement @ 125 PSIG	icfm	23.5						47						
CFM Displacement @ 175 PSIG	icfm	21.4						42.8						
Maximum Pressure	psig	175												
Working Pressure Differential	psig	35												
Pump Operating Speed @ 125 PSIG	rpm	750												
Pump Operating Speed @ 175 PSIG	rpm	710												
Minimum Speed	rpm	400												
Maximum Speed	rpm	1050												
Cooling Air Flow @ 125 PSIG	cfm	868												
Cooling Air Flow @ 175 PSIG	cfm	820												
Heat Rejection	btu/hr	12000												
Noise Level (8)	dB(A)	75						78						
Aftercooler Approach Temp (9)	°F	45												
Min/Max Operating Temp	°F	32/104												
Dimensions and Weight														
Tank Size	gal	na	60	80	120	30	60	80	120	80	120	250		
Tank Configuration	na	na	Vertical				Horizontal							
Tank Capacity @ 125 PSIG	ft³	na	68.4	91.1	136.7	34.2	68.4	91.1	136.7	91.1	136.7	284.9		
Tank Capacity @ 175 PSIG	ft³	na	95.7	127.6	191.4	47.8	95.7	127.6	191.4	127.6	191.4	398.8		
Tank Pumping Time @ 125 PSIG (10)	min	na	3.6	4.8	7.1	1.8	3.6	4.8	7.1	2.4	3.6	7.4		
Tank Pumping Time @ 175 PSIG (10)	min	na	5.5	7.4	11.0	2.8	5.5	7.4	11.0	3.7	5.5	11.5		
Package Length	in.	38.0	35.3	35.0	35.3	42.6	51.8	66.8	71.5	74.9	74.9	88.3		
Package Width	in.	24.7	32.5	34.5	37.4	31.4	31.6	31.6	32.8	31.7	32.7	37.9		
Package Height	in.	29.5	77.4	76.4	75.8	43.7	49.3	48.8	54.8	49.8	54.0	60.5		
Approx. Ship Weight	lbs.	280	525	590	762	432	525	590	762	755	980	1140		
Pump Length	in.	20												
Pump Width	in.	16.5												
Pump Height	in.	23.25												
Pump Weight	lbs.	109												
Discharge Connection (11)	npt "	3/4	1/2 F		3/4 F		1/2 F		3/4 F		1/2		3/4 F	
Operating/Parts Manual ID	na	CQGF3454												

6) All units tested in accordance with CAGI/PNEUROP Acceptance Test Code PN2CPTC2.
 7) acfm is actual cubic feet per minute at inlet conditions.
 8) Sound levels are based off estimated dB(A) .
 9) Approach temperature is the temperature above the discharge air and above the ambient air of the aftercooler.
 10) Tank pumping time is based off 0 PSIG to fully pressurized.
 11) M = Male connection, F=Female connection

NOTE: Duplex models take quantities of 2 on applicable items such as motors, pump, oil quantity, etc.

Due to Gardner Denver's continuing product development program, specifications and materials are subject to change without notice or obligation.