

**CHAMPION**

PL-SERIES | 15 HP RECIPROCATING COMPRESSORS

## Pump Model PL-40A

### The Solution to Your Application

Champion PL-Series pressure lubricated compressors offer rugged standard features, a wide selection of configurations, quality available options, and a time-tested design. High performance, long life and tremendous value make Champion compressors the proven solution to your application.

### Standard Features

- Magnetic Starter
- Loadless starting (via hydraulic unloader)
- Dual control
- ASME pressure relief valve
- ODP NEMA 1760 RPM motor
- 10 Micron intake air filter
- ASME coded receiver
- 0-300 PSIG air pressure gauge
- Available voltages
  - 1 Phase—115/208-230
  - 3 Phase—208/230/460/575
- 1-Year package warranty
- 5-Year pro-rated pump warranty

### Available Options

- Multiple tank sizes and variations
- Electric or engine driven
- NEMA 4 full-voltage starter upgrade
- Premium efficiency motor upgrades
- Control panel upgrades
- Aftercooler with or without moisture separator
- Low oil-pressure switch (NEMA 1 or 4)
- Vibration isolators
- High temperature switch (NEMA 1 or 4)
- Available switches (NEMA 1 or 4)
  - Hand/Off/Auto, Off/On
- Pneumatic or electric tank drain



## BARE PUMP

MODEL	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	DISPL./REV. CUBIC FEET	BORE DIA. INCHES	STROKE INCHES	# OF CYLINDERS	OIL CAPACITY QTS.	MIN/MAX PUMP RPM
PL-40A	32 x 27.5 x 30	440	0.142	6.3 & 3.3	4.5	2	4	425/1000

## BASE MOUNTED UNITS

MOTOR HP	PL-SERIES CBBPLA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	125 PSI RATING		175 PSI RATING		250 PSI RATING	
				RPM	CFM DEL'Y	RPM	CFM DEL'Y	RPM	CFM DEL'Y
15	BPL15	49.5 x 27.5 x 38	730	890	59	770	53.7	700	45.8

## SIMPLEX HORIZONTAL TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	PL-SERIES CBSPLA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	125 PSI RATING		175 PSI RATING		250 PSI RATING	
					RPM	CFM DEL'Y	RPM	CFM DEL'Y	RPM	CFM DEL'Y
15	120	HPL15-12	72 x 27.5 x 62	1110	890	59	770	53.7	700	45.8
15	250	HPL15-25	89 x 30.3 x 69	1495	890	59	770	53.7	700	45.8

## DUPLEX TANK MOUNTED UNITS

MOTOR HP	TANK CAPACITY GAL.	PL-SERIES CBDPLA	DIMENSIONS L x W x H INCHES	APPROX. SHIP WEIGHT LBS.	125 PSI RATING		175 PSI RATING		250 PSI RATING	
					RPM	CFM DEL'Y	RPM	CFM DEL'Y	RPM	CFM DEL'Y
15 (2)	250	HPL15D-25	89 x 55.6 x 73.5	2460	890	118	770	107.4	700	91.6

Simplex CFM values are doubled for duplex units. Duplex units have two motors and two pumps on one tank.



1301 North Euclid Avenue  
Princeton, Illinois 61356 USA  
[www.ChampionPneumatic.com/ContactUs.aspx](http://www.ChampionPneumatic.com/ContactUs.aspx)  
866-276-4330  
[www.ChampionPneumatic.com](http://www.ChampionPneumatic.com)



©2015 Gardner Denver, Inc. Printed in U.S.A.  
CR-PL-PL40 1st Ed. 11/15

Product specifications and materials are subject to change without notice.

